

# SOLID TECH

## Rack of Silence

Rack of Silence offers the optimal form and function to accommodate your equipment.

Its versatile and functional design guarantees minimum resonance and vibration.

The Apparatus Support system is made of extruded aluminum which controls efficiently the resonance as both inside and outside are coated with acrylic glass and insulated from the wooden strut with a cork lined underside. Moreover is the top cork

lined and offers a scratch resistance to the apparatus as well as resonance-free surface to be placed upon.

On top of the Apparatus Support, an optional table can be placed in order to achieve a more traditional rack look.

A top shelf made of a unique sandwich board, especially developed for acoustic damping, with matching veneers. Such top

shelf can be supported by Solid Tech isolator, Discs of Silence.

Rack of Silence Reference line has a unique integrated isolation system with revolutionary capability of decoupling both vertical and horizontal. The Rack of Silence series is available in black or silver anodized aluminum and there are several wood trim veneers as well as lacquers.



# Rack of Silence variants and options

## Rack of Silence Reference (with isolation integrated)



**ROS 4 Ref.**

Outer dimensions: 900x500x700mm (HxDxW)  
Between pillars: 520mm  
Total available space in-between strut shelves: 595mm  
2x Max load basic strut shelf: 40kg  
2x Max load HD strut shelf: 80kg



**ROS 3 Ref.**


Outer dimensions: 600x500x700mm (HxDxW)  
Between pillars: 520mm  
Total available space in-between strut shelves: 380mm  
2x Max load basic strut shelf: 40kg  
1x Max load HD strut shelf: 80kg



**ROS 1 Ref.**

Outer dimensions: 300x500x700mm (HxDxW)  
Between pillars: 520mm  
1x Max load basic strut shelf: 40kg

## Rack of Silence Regular (without isolation)



**ROS 4 Reg.**

Outer dimensions: 900x500x700mm (HxDxW)  
Between pillars: 520mm  
Total available space in-between strut shelves: 595mm  
2x Max load basic strut shelf: 40kg  
2x Max load HD strut shelf: 80kg



**ROS 3 Reg.**

Outer dimensions: 600x500x700mm (HxDxW)  
Between pillars: 520mm  
Total available space in-between strut shelves: 380mm  
2x Max load basic strut shelf: 40kg  
1x Max load HD strut shelf: 80kg



**ROS 2 Reg.**

Outer dimensions: 600x500x700mm (HxDxW)  
Between pillars: 520mm  
Total available space in-between shelves: 435mm  
1x Max load basic strut shelf: 40kg  
1x Max load HD strut shelf: 80kg



**ROS 1 Reg.**

Outer dimensions: 300x500x700mm (HxDxW)  
Between pillars: 520mm  
1x Max load HD strut shelf: 80kg

## Strut color options



Black structure



White structure



Cherry



Walnut



Mocha

## Extrusion color options



Extrusion in silver and black anodized aluminum

## Optional Small and Large Top Tables



Top table "large" in black, white, walnut, cherry and Mocha

Top table "small" in black, white, walnut, cherry and Mocha

## Isolation system



Integrated Isolation (Reference)



Isolator Support



Top shelf isolator

## Optional floor protectors



Spike Fixed Floor Protector



Feet of Concrete



Floor Protector

# SOLID TECH

info@solid-tech.net  
www.solid-tech.net  
+46(0)40 491352

Sporregatan 25, SE-21377 Malmö, Sweden

**More information and distributor list  
is available in homepage**